

Developer's Guide

to

the PARI library

(version 2.9.4)

The PARI Group

Institut de Mathématiques de Bordeaux, UMR 5251 du CNRS.
Université de Bordeaux, 351 Cours de la Libération
F-33405 TALENCE Cedex, FRANCE
e-mail: `pari@math.u-bordeaux.fr`

Home Page:
`http://pari.math.u-bordeaux.fr/`

Copyright © 2000–2017 The PARI Group

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions, or translations, of this manual under the conditions for verbatim copying, provided also that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

PARI/GP is Copyright © 2000–2017 The PARI Group

PARI/GP is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation. It is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY WHATSOEVER.

Table of Contents

Chapter 1: Work in progress	5
1.1 The type <code>t_CLOSURE</code>	5
1.1.1 Debugging information in closure	6
1.2 The type <code>t_LIST</code>	6
1.2.1 Maps as Lists	7
1.3 Protection of non-interruptible code	8
1.3.1 Multithread interruptions	8
1.4 \mathbf{F}_l^2 field for small primes l	9
1.5 Public functions useless outside of GP context	9
1.5.1 Conversions	9
1.5.2 Output	9
1.5.3 Input	10
1.5.4 Control flow statements	10
1.5.5 Accessors	10
1.5.6 Iterators	10
1.5.7 Local precision	11
1.5.8 Functions related to the GP evaluator	11
1.5.9 Miscellaneous	11
1.6 Embedded GP interpreter	12
Chapter 2: Regression tests, benches	12
2.1 Functions for GP2C	13
2.1.1 Functions for safe access to components	13
Chapter 3: Parallelism	13
3.1 The PARI MT interface	13
3.1.1 Miscellaneous	14
3.2 Initialization	14
Index	15

Chapter 1:

Work in progress

This draft documents private internal functions and structures for hard-core PARI developers. Anything in here is liable to change on short notice. Don't use anything in the present document, unless you are implementing new features for the PARI library. Try to fix the interfaces before using them, or document them in a better way. If you find an undocumented hack somewhere, add it here.

Hopefully, this will eventually document everything that we buried in `paripriv.h` or even more private header files like `anal.h`. Possibly, even implementation choices! Way to go.

1.1 The type `t_CLOSURE`.

This type holds closures and functions in compiled form, so is deeply linked to the internals of the GP compiler and evaluator. The length of this type can be 6, 7 or 8 depending whether the object is an “inline closure”, a “function” or a “true closure”.

A function is a regular GP function. The GP input line is treated as a function of arity 0.

A true closure is a GP function defined in a non-empty lexical context.

An inline closure is a closure that appears in the code without the preceding `->` token. They are generally attached to the prototype code 'E' and 'I'. Inline closures can only exist as data of other closures, see below.

In the following example,

```
f(a=Euler)=x->sin(x+a);
g=f(Pi/2);
plot(x=0,2*Pi,g(x))
```

`f` is a function, `g` is a true closure and both `Euler` and `g(x)` are inline closures.

This type has a second codeword `z[1]`, which is the arity of the function or closure. This is zero for inline closures. To access it, use

```
long closure_arity(GEN C)
```

- `z[2]` points to a `t_STR` which holds the opcodes. To access it, use

```
GEN closure_get_code(GEN C).
```

`const char * closure_codestr(GEN C)` returns as an array of `char` starting at 1.

- `z[3]` points to a `t_VECSMALL` which holds the operands of the opcodes. To access it, use

```
GEN closure_get_oper(GEN C)
```

• `z[4]` points to a `t_VEC` which hold the data referenced by the `pushgen` opcodes, which can be `t_CLOSURE`, and in particular inline closures. To access it, use

```
GEN closure_get_data(GEN C)
```

- `z[5]` points to a `t_VEC` which hold extra data needed for error-reporting and debugging. See Section 1.1.1 for details. To access it, use

```
GEN closure_get_dbg(GEN C)
```

Additionally, for functions and true closures,

- `z[6]` usually points to a `t_VEC` with two components which are `t_STR`. The first one displays the list of arguments of the closure without the enclosing parentheses, the second one the GP code of the function at the right of the `->` token. They are used to display the closure, either in implicit or explicit form. However for closures that were not generated from GP code, `z[6]` can point to a `t_STR` instead. To access it, use

```
GEN closure_get_text(GEN C)
```

Additionally, for true closure,

- `z[7]` points to a `t_VEC` which holds the values of all lexical variables defined in the scope the closure was defined. To access it, use

```
GEN closure_get_frame(GEN C)
```

1.1.1 Debugging information in closure.

Every `t_CLOSURE` object `z` has a component `dbg=z[5]` which hold extra data needed for error-reporting and debugging. The object `dbg` is a `t_VEC` with 3 components:

`dbg[1]` is a `t_VECSMALL` of the same length than `z[3]`. For each opcode, it holds the position of the corresponding GP source code in the strings stored in `z[6]` for function or true closures, positive indices referring to the second strings, and negative indices referring to the first strings, the last element being indexed as `-1`. For inline closures, the string of the parent function or true closure is used instead.

`dbg[2]` is a `t_VECSMALL` that lists opcodes index where new lexical local variables are created. The value 0 denotes the position before the first offset and variables created by the prototype code 'V'.

`dbg[3]` is a `t_VEC` of `t_VECSMALLs` that give the list of `entree*` of the lexical local variables created at a given index in `dbg[2]`.

1.2 The type `t_LIST`.

This type needs to go through various hoops to support GP's inconvenient memory model. Don't use `t_LISTs` in pure library mode, reimplement ordinary lists! This dynamic type is implemented by a `GEN` of length 3: two codewords and a vector containing the actual entries. In a normal setup (a finished list, ready to be used),

- the vector is malloc'ed, so that it can be realloc'ated without moving the parent `GEN`.
- all the entries are clones, possibly with cloned subcomponents; they must be deleted with `gunclone_deep`, not `gunclone`.

The following macros are proper lvalues and access the components

`long list_nmax(GEN L)`: current maximal number of elements. This grows as needed.

GEN `list_data`(GEN `L`): the elements. If `v = list_data(L)`, then either `v` is NULL (empty list) or `l = lg(v)` is defined, and the elements are `v[1], ..., v[l-1]`.

In most `gerepile` scenarios, the list components are not inspected and a shallow copy of the malloc'ed vector is made. The functions `gclone`, `copy_bin_canon` are exceptions, and make a full copy of the list.

The main problem with lists is to avoid memory leaks; in the above setup, a statement like `a = List(1)` would already leak memory, since `List(1)` allocates memory, which is cloned (second allocation) when assigned to `a`; and the original list is lost. The solution we implemented is

- to create anonymous lists (from `List`, `gtolist`, `concat` or `vecsor`) entirely on the stack, *not* as described above, and to set `list_nmax` to 0. Such a list is not yet proper and trying to append elements to it fails:

```
? listput(List(),1)
***   variable name expected: listput(List(),1)
***                                     ^-----
```

If we had been malloc'ing memory for the `List([1,2,3])`, it would have leaked already.

- as soon as a list is assigned to a variable (or a component thereof) by the GP evaluator, the assigned list is converted to the proper format (with `list_nmax` set) previously described.

GEN `listcopy`(GEN `L`) return a full copy of the `t_LIST` `L`, allocated on the *stack* (hence `list_nmax` is 0). Shortcut for `gcopy`.

GEN `mklistcopy`(GEN `x`) returns a list with a single element `x`, allocated on the stack. Used to implement most cases of `gtolist` (except vectors and lists).

A typical low-level construct:

```
long l;
/* assume L is a t_LIST */
L = list_data(L); /* discard t_LIST wrapper */
l = L? lg(L): 1;
for (i = 1; i < l; i++) output( gel(L, i) );
for (i = 1; i < l; i++) gel(L, i) = gclone( ... );
```

1.2.1 Maps as Lists.

GP's maps are implemented on top of `t_LIST`s so as to benefit from their peculiar memory models. Lists thus come in two subtypes: `t_LIST_RAW` (actual lists) and `t_LIST_MAP` (a map).

GEN `mklist_typ`(long `t`) create a list of subtype `t`. GEN `mklist`(void) is an alias for

```
mklist_typ(t_LIST_RAW);
```

and GEN `mkmap`(void) is an alias for

```
mklist_typ(t_LIST_MAP);
```

long `list_typ`(GEN `L`) return the list subtype, either `t_LIST_RAW` or `t_LIST_MAP`.

void `listpop`(GEN `L`, long `index`) as `listpop0`, assuming that `L` is a `t_LIST_RAW`.

GEN `listput`(GEN `list`, GEN `object`, long `index`) as `listput0`, assuming that `L` is a `t_LIST_RAW`.

GEN `mapdomain`(GEN `T`) vector of keys of the map `T`.

GEN `mapdomain_shallow`(GEN `T`) shallow version of `mapdomain`.

GEN `maptomat`(GEN `T`) convert a map to a factorization matrix.

GEN `maptomat_shallow`(GEN `T`) shallow version of `maptomat`.

1.3 Protection of non-interruptible code.

GP allows the user to interrupt a computation by issuing `SIGINT` (usually by entering control-C) or `SIGALRM` (usually using `alarm()`). To avoid such interruption to occurs in section of code which are not reentrant (in particular `malloc` and `free`) the following mechanism is provided:

`BLOCK_SIGINT_START()` Start a non-interruptible block code. Block both `SIGINT` and `SIGALRM`.

`BLOCK_SIGALRM_START()` Start a non-interruptible block code. Block only `SIGALRM`. This is used in the `SIGINT` handler itself to delay an eventual pending alarm.

`BLOCK_SIGINT_END()` End a non-interruptible block code

The above macros make use of the following global variables:

`PARI_SIGINT_block`: set to 1 (resp. 2) by `BLOCK_SIGINT_START` (resp. `BLOCK_SIGALRM_START`).

`PARI_SIGINT_pending`: Either 0 (no signal was blocked), `SIGINT` (`SIGINT` was blocked) or `SIGALRM` (`SIGALRM` was blocked). This need to be set by the signal handler.

Within a block, an automatic variable `int block` is defined which records the value of `PARI_SIGINT_block` when entering the block.

1.3.1 Multithread interruptions.

To support multithreaded programs, `BLOCK_SIGINT_START` and `BLOCK_SIGALRM_START` call `MT_SIGINT_BLOCK(block)`, and `BLOCK_SIGINT_END` calls `MT_SIGINT_UNBLOCK(block)`.

`MT_SIGINT_BLOCK` and `MT_SIGINT_UNBLOCK` are defined by the multithread engine. They can calls the following public functions defined by the multithread engine.

```
void mt_sigint_block(void)
```

```
void mt_sigint_unblock(void)
```

In practice this mechanism is used by the POSIX thread engine to protect against asynchronous cancellation.

1.4 \mathbf{F}_{l^2} field for small primes l .

Let $l > 2$ be a prime `ulong`. A `F12` is an element of the finite field \mathbf{F}_{l^2} represented (currently) by a `Flx` of degree at most 1 modulo a polynomial of the form $x^2 - D$ for some non square $0 \leq D < p$. Below `pi` denotes the pseudo inverse of `p`, see `Fl_mul_pre`

`int F12_equal1(GEN x)` return 1 if $x = 1$, else return 0.

`GEN F12_mul_pre(GEN x, GEN y, ulong D, ulong p, ulong pi)` return xy .

`GEN F12_sqr_pre(GEN x, ulong D, ulong p, ulong pi)` return x^2 .

`GEN F12_inv_pre(GEN x, ulong D, ulong p, ulong pi)` return x^{-1} .

`GEN F12_pow_pre(GEN x, GEN n, ulong D, ulong p, ulong pi)` return x^n .

`GEN F12_sqrtn_pre(GEN a, GEN n, ulong D, ulong p, ulong pi, GEN *zeta)` n -th root, as `Flxq_sqrtn`.

`GEN F12_norm_pre(GEN x, GEN n, ulong D, ulong p, ulong pi)` return the norm of x .

`GEN Flx_F12_eval_pre(GEN P, GEN x, ulong D, ulong p, ulong pi)` return $P(x)$.

1.5 Public functions useless outside of GP context.

These functions implement GP functionality for which the C language or other libpari routines provide a better equivalent; or which are so tied to the `gp` interpreter as to be virtually useless in libpari. Some may be generated by `gp2c`. We document them here for completeness.

1.5.1 Conversions.

`GEN toser_i(GEN x)` internal shallow function, used to implement automatic conversions to power series in GP (as in `cos(x)`). Converts a `t_POL` or a `t_RFRAC` to a `t_SER` in the same variable and precision `precdbl` (the global variable corresponding to `seriesprecision`). Returns x itself for a `t_SER`, and `NULL` for other argument types. The fact that it uses a global variable makes it awkward whenever you're not implementing a new transcendental function in GP. Use `RgX_to_ser` or `rfrac_to_ser` for a fast clean alternative to `gtoser`.

1.5.2 Output.

`void print0(GEN g, long flag)` internal function underlying the `print` GP function. Prints the entries of the `t_VEC` g , one by one, without any separator; entries of type `t_STR` are printed without enclosing quotes. *flag* is one of `f_RAW`, `f_PRETTYMAT` or `f_TEX`, using the current default output context.

`void out_print0(PariOUT *out, const char *sep, GEN g, long flag)` as `print0`, using output context `out` and separator `sep` between successive entries (no separator if `NULL`).

`void printsep(const char *s, GEN g, long flag)` `out_print0` on `pariOut` followed by a newline.

`void printsep1(const char *s, GEN g, long flag)` `out_print0` on `pariOut`.

`char* pari_sprint0(const char *s, GEN g, long flag)` displays s , then `print0(g, flag)`.

`void print(GEN g)` equivalent to `print0(g, f_RAW)`, followed by a `\n` then an `fflush`.

void print1(GEN g) as above, without the `\n`. Use `pari_printf` or `output` instead.

void printtex(GEN g) equivalent to `print0(g, t_TEX)`, followed by a `\n` then an `fflush`. Use `GENtoTeXstr` and `pari_printf` instead.

void write0(const char *s, GEN g)

void write1(const char *s, GEN g) use `fprintf`

void writetex(const char *s, GEN g) use `GENtoTeXstr` and `fprintf`.

void printf0(GEN fmt, GEN args) use `pari_printf`.

GEN Strprintf(GEN fmt, GEN args) use `pari_sprintf`.

1.5.3 Input.

gp's input is read from the stream `pari_infile`, which is changed using

```
FILE* switchin(const char *name)
```

Note that this function is quite complicated, maintaining stacks of files to allow smooth error recovery and gp interaction. You will be better off using `gp_read_file`.

1.5.4 Control flow statements.

GEN break0(long n). Use the C control statement `break`. Since `break(2)` is invalid in C, either rework your code or use `goto`.

GEN next0(long n). Use the C control statement `continue`. Since `continue(2)` is invalid in C, either rework your code or use `goto`.

GEN return0(GEN x). Use `return`!

void error0(GEN g). Use `pari_err(e_USER,)`

void warning0(GEN g). Use `pari_warn(e_USER,)`

1.5.5 Accessors.

GEN vecslice0(GEN A, long a, long b) implements $A[a..b]$.

GEN matslice0(GEN A, long a, long b, long c, long d) implements $A[a..b, c..d]$.

1.5.6 Iterators.

GEN apply0(GEN f, GEN A) gp wrapper calling `genapply`, where f is a `t_CLOSURE`, applied to A . Use `genapply` or a standard C loop.

GEN select0(GEN f, GEN A) gp wrapper calling `genselect`, where f is a `t_CLOSURE` selecting from A . Use `genselect` or a standard C loop.

GEN vecapply(void *E, GEN (*f)(void* E, GEN x), GEN x) implements $[a(x) | x \leftarrow b]$.

GEN veccatapply(void *E, GEN (*f)(void* E, GEN x), GEN x) implements `concat([a(x) | x <- b])` which used to implement $[a_0(x, y) | x \leftarrow b; y \leftarrow c(b)]$ which is equal to `concat([a_0(x, y) | y <- c(b)] | x <- b]`.

GEN vecselect(void *E, long (*f)(void* E, GEN x), GEN A) implements $[x \leftarrow b, c(x)]$.

GEN vecselapply(void *Epred, long (*pred)(void* E, GEN x), void *Efun, GEN (*fun)(void* E, GEN x), GEN A) implements $[a(x) | x \leftarrow b, c(x)]$.

1.5.7 Local precision.

These functions allow to change `realprecision` locally when calling the GP interpreter.

`void push_localprec(long p)` set the local precision to p .

`void push_localbitprec(long b)` set the local precision to b bits.

`void pop_localprec(void)` reset the local precision to the previous value.

`long get_localprec(void)` returns the current local precision.

`long get_localbitprec(void)` returns the current local precision in bits.

`void localprec(long p)` trivial wrapper around `push_localprec` (sanity checks and convert from decimal digits to a number of codewords). Use `push_localprec`.

`void localbitprec(long p)` trivial wrapper around `push_localbitprec` (sanity checks). Use `push_localbitprec`.

1.5.8 Functions related to the GP evaluator.

The prototype code `C` instructs the GP compiler to save the current lexical context (pairs made of a lexical variable name and its value) in a `GEN`, called `pack` in the sequel. This `pack` can be used to evaluate expressions in the corresponding lexical context, providing it is current.

`GEN localvars_read_str(const char *s, GEN pack)` evaluate the string s in the lexical context given by `pack`. Used by `geval_gp` in GP to implement the behaviour below:

```
? my(z=3);eval("z=z^2");z
%1 = 9
```

`long localvars_find(GEN pack, entree *ep)` does `pack` contain a pair whose variable corresponds to `ep`? If so, where is the corresponding value? (returns an offset on the value stack).

1.5.9 Miscellaneous.

`char* os_getenv(const char *s)` either calls `getenv`, or directly return `NULL` if the `libc` does not provide it. Use `getenv`.

`sighandler_t os_signal(int sig, pari_sighandler_t fun)` after a

```
typedef void (*pari_sighandler_t)(int);
```

(private type, not exported). Installs signal handler `fun` for signal `sig`, using `sigaction` with flag `SA_NODEFER`. If `sigaction` is not available use `signal`. If even the latter is not available, just return `SIG_IGN`. Use `sigaction`.

1.6 Embedded GP interpreter.

These functions provide a simplified interface to embed a GP interpreter in a program.

`void gp_embedded_init(long rsize, long vsize)` Initialize the GP interpreter (like `pari_init` does) with `parisize=rsize` and `parisizemax=vsize`.

`char * gp_embedded(const char *s)` Evaluate the string `s` with GP and return the result as a string, in a format similar to what GP displays (with the history index). The resulting string is allocated on the PARI stack, so subsequent call to `gp_embedded` will destroy it.

Chapter 2:

Regression tests, benches

This chapter documents how to write an automated test module, say `fun`, so that `make test-fun` executes the statements in the `fun` module and times them, compares the output to a template, and prints an error message if they do not match.

- Pick a *new* name for your test, say `fun`, and write down a GP script named `fun`. Make sure it produces some useful output and tests adequately a set of routines.

- The script should not be too long: one minute runs should be enough. Try to break your script into independent easily reproducible tests, this way regressions are easier to debug; e.g. include `setrand(1)` statement before a randomized computation. The expected output may be different on 32-bit and 64-bit machines but should otherwise be platform-independent. If possible, the output shouldn't even depend on `sizeof(long)`; using a `realprecision` that exists on both 32-bit and 64-bit architectures, e.g. `\p 38` is a good first step.

- Dump your script into `src/test/in/` and run `Configure`.

- `make test-fun` now runs the new test, producing a [BUG] error message and a `.dif` file in the relevant object directory `Oxxx`. In fact, we compared the output to a non-existing template, so this must fail.

- Now

```
patch -p1 < Oxxx/fun.dif
```

generates a template output in the right place `src/test/32/fun`, for instance on a 32-bit machine.

- If different output is expected on 32-bit and 64-bit machines, run the test on a 64-bit machine and patch again, thereby producing `src/test/64/fun`. If, on the contrary, the output must be the same, make sure the output template land in the `src/test/32/` directory (which provides a default template when the 64-bit output file is missing); in particular move the file from `src/test/64/` to `src/test/32/` if the test was run on a 64-bit machine.

- You can now re-run the test to check for regressions: no [BUG] is expected this time! Of course you can at any time add some checks, and iterate the test / patch phases. In particular, each time a bug in the `fun` module is fixed, it is a good idea to add a minimal test case to the test suite.

- By default, your new test is now included in `make test-all`. If it is particularly annoying, e.g. opens tons of graphical windows as `make test-ploth` or just much longer than the recommended minute, you may edit `config/get_tests` and add the `fun` test to the list of excluded tests, in the `test_extra_out` variable.

- The `get_tests` script also defines the recipe for `make bench` timings, via the variable `test_basic`. A test is included as `fun` or `fun_n`, where n is an integer ≤ 1000 ; the latter means that the timing is weighted by a factor $n/1000$. (This was introduced a long time ago, when the `nfields` bench was so much slower than the others that it hid slowdowns elsewhere.)

2.1 Functions for GP2C.

2.1.1 Functions for safe access to components.

This function returns the address of the requested component after checking it is actually valid. This is used by GP2C -C.

`GEN* safegel(GEN x, long l)`, safe version of `gel(x,l)` for `t_VEC`, `t_COL` and `t_MAT`.

`long* safeel(GEN x, long l)`, safe version of `x[l]` for `t_VECSMALL`.

`GEN* safelistel(GEN x, long l)` safe access to `t_LIST` component.

`GEN* safegcoeff(GEN x, long a, long b)` safe version of `gcoeff(x,a, b)` for `t_MAT`.

Chapter 3:

Parallelism

3.1 The PARI MT interface.

PARI provides an abstraction for doing parallel computations.

`void mt_queue_start(struct pari_mt *pt, GEN worker)` Let `worker` be a `t_CLOSURE` object of arity 1. Initialize the structure `pt` to evaluate `worker` in parallel.

`void mt_queue_submit(struct pari_mt *pt, long taskid, GEN task)` Submit `task` to be evaluated by `worker`, or `NULL` if no further task is left to be submitted. The value `taskid` is user-specified and allows to later match up results and submitted tasks.

`GEN mt_queue_get(struct pari_mt *pt, long *taskid, long *pending)` Return the result of the evaluation by `worker` of one of the previously submitted tasks. Set `pending` to the number of remaining pending tasks. Set `taskid` to the value associate to this task by `mt_queue_submit`. Returns `NULL` if more tasks need to be submitted.

`void mt_queue_end(struct pari_mt *pt)` End the parallel execution.

Calls to `mt_queue_submit` and `mt_queue_get` must alternate: each call to `mt_queue_submit` must be followed by a call to `mt_queue_get` before any other call to `mt_queue_submit`, and conversely.

The first call to `mt_queue_get` will return `NULL` until a sufficient number of tasks have been submitted. If no more tasks are left to be submitted, use

```
mt_queue_submit(handle, id, NULL)
```

to allow further calls to `mt_queue_get`. If `mt_queue_get` sets `pending` to 0, then no more tasks are pending and it is safe to call `mt_queue_end`.

The parameter `taskid` can be chosen arbitrarily. It is attached to a task but is not available to `worker`. It provides an efficient way to match a tasks and results. It is ignored when the parameter `task` is `NULL`.

3.1.1 Miscellaneous.

`void mt_broadcast(GEN code)`: do nothing unless the MPI threading engine is in use. In that case, it evaluates the closure `code` on all secondary nodes. This can be used to change the states of the MPI child nodes. This is used by `install`.

3.2 Initialization.

This section is technical.

`void pari_mt_init(void)` When using MPI, it is sometimes necessary to run initialization code on the child nodes after PARI is initialized. This can be done as follow:

- call `pari_init_opts` with the flag `INIT_noIMTm`. This initializes PARI, but not the MT engine.
- call the required initialization code.
- call `pari_mt_init` to initialize the MT engine. Note that under MPI, this function only returns on the master node. On the child nodes, it enters slave mode. Thus it is no longer possible to run initialization code on the child nodes.

See the file `examples/pari-mt.c` for an example.

`void pari_mt_close(void)` When using MPI, calling `pari_close` will terminate the MPI execution environment. If this is undesirable, you should call `pari_close_opts` with the flag `INIT_noIMTm`. This closes PARI without terminating the MPI execution environment. It is allowed to call `pari_mt_close` later to terminate it. Note that the once MPI is terminated it cannot be restarted, and that it is considered an error for a program to end without having terminated the MPI execution environment.

Index

SomeWord refers to PARI-GP concepts.
SomeWord is a PARI-GP keyword.
SomeWord is a generic index entry.

A

apply0 10

B

BLOCK_SIGALRM_START 8
BLOCK_SIGINT_END 8
BLOCK_SIGINT_START 8
break0 10

C

closure 5
closure_arity 5
closure_codestr 5
closure_get_code 5
closure_get_data 5
closure_get_dbg 5
closure_get_frame 6
closure_get_oper 5
closure_get_text 6

E

error0 10

F

F12_equal1 8
F12_inv_pre 8
F12_mul_pre 8
F12_norm_pre 8
F12_pow_pre 8
F12_sqrtn_pre 8
F12_sqr_pre 8
Flx_F12_eval_pre 9
f_PRETTYMAT 9
f_RAW 9
f_TEX 9

G

genapply 10
genselect 10
GENToTeXstr 9, 10
getenv 11
get_localbitprec 11
get_localprec 11

geval_gp 11
gp_embedded 11
gp_embedded_init 11
gp_read_file 10
gunclone 6
gunclone_deep 6

I

INIT_noIMTm 14
install 14

L

list 6
listcopy 7
listpop 7
listput 7
list_data 6
list_nmax 6
list_typ 7
localbitprec 11
localprec 11
localvars_find 11
localvars_read_str 11

M

mapdomain 7
mapdomain_shallow 7
maptomat 7
maptomat_shallow 8
matslice0 10
mklist 7
mklistcopy 7
mklist_typ 7
mkmap 7
mt_broadcast 14
mt_queue_end 13
mt_queue_get 13
mt_queue_start 13
mt_queue_submit 13
MT_SIGINT_BLOCK 8
mt_sigint_block 8
MT_SIGINT_UNBLOCK 8
mt_sigint_unblock 8

N

next0 10

O

os_getenv	11
os_signal	11
output	9
out_print0	9

P

pariOut	9
pari_close	14
pari_close_opts	14
pari_infile	10
pari_init_opts	14
pari_mt_close	14
pari_mt_init	14
pari_printf	9, 10
PARI_SIGINT_block	8
PARI_SIGINT_pending	8
pari_sprint0	9
pari_sprintf	10
pop_localprec	11
print	9
print0	9
print1	9
printf0	10
printsep	9
printsep1	9
printtex	9
push_localbitprec	11
push_localprec	10

R

return0	10
rfrac_to_ser	9
RgX_to_ser	9

S

safeel	13
safegcoeff	13
safegel	13
safelistel	13
SA_NODEFER	11
select0	10
sigaction	11
signal	11
SIG_IGN	11
Strprintf	10
switchin	10

T

toser_i	9
t_CLOSURE	5
t_LIST	6

V

vecapply	10
veccatapply	10
vecselapply	10
vecselect	10
vecslic0	10

W

warning0	10
write0	9
writel	9
writetex	10